


SIDECAR S PRO

“Sidecar is our most compact version of spotlights. It is a traditional side-by-side solution, inspired by the sidecar version of a motorcycle. We created a design that places the point of rotation on the track as central as possible to avoid a big offset from the track, allowing a number of spotlights to visually work well together. Developed and produced in Sweden”.


LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral premium driver.
Low ripple output current <4% to assure camera and scanner friendly performance.
Rotation 365°. Vertical adjustment +/- 90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	760g
Reflector	High purity aluminium
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 34pcs/MCB 16A type B
Ripple out. current	< 4%. Flicker-free performance
Colour consistency	3 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Not dimmable



- White
- Black



Accessories

Honeycomb louvre Sidecar S **213091**

SIDECAR S PRO

Description	Reflector	CCT (K)	CRI	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																																																																																
				LIGHTSOURCE				ART. No.																																																																																																																	
WARM WHITE 3000K (930)																																																																																																																									
SIDECAR S Pro 2000lm SP 930	Spot 15°	3000K	92	2510	19W	2310	121	213110	213114																																																																																																																
SIDECAR S Pro 2000lm ME 930	Medium 25°	3000K	92	2510	19W	2310	121	213111	213115																																																																																																																
SIDECAR S Pro 2000lm FL 930	Flood 40°	3000K	92	2510	19W	2310	121	213112	213116																																																																																																																
SIDECAR S Pro 2000lm WFL 930	Widefl. 60°	3000K	92	2510	19W	2310	121	213113	213117																																																																																																																
SIDECAR S Pro 3000lm SP 930																																																																																																																									
SIDECAR S Pro 3000lm ME 930	Medium 25°	3000K	92	3530	27W	3250	120	213210	213214																																																																																																																
SIDECAR S Pro 3000lm FL 930	Flood 40°	3000K	92	3530	27W	3250	120	213211	213215																																																																																																																
SIDECAR S Pro 3000lm FL 930	Flood 40°	3000K	92	3530	27W	3250	120	213212	213216																																																																																																																
SIDECAR S Pro 3000lm WFL 930	Widefl. 60°	3000K	92	3530	27W	3250	120	213213	213217																																																																																																																
<table border="1"> <thead> <tr> <th colspan="4">Spot</th> <th colspan="4">Medium</th> <th colspan="4">Flood</th> <th colspan="4">Wideflood</th> </tr> <tr> <th colspan="2"></th> <th>2000lm</th> <th>3000lm</th> <th colspan="2"></th> <th>2000lm</th> <th>3000lm</th> <th colspan="2"></th> <th>2000lm</th> <th>3000lm</th> <th colspan="2"></th> <th>2000lm</th> <th>3000lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>14960</td> <td>21047</td> <td>1</td> <td>0,42</td> <td>8328</td> <td>11716</td> <td>1</td> <td>0,74</td> <td>4763</td> <td>6702</td> <td>1</td> <td>1,19</td> <td>2539</td> <td>3572</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>3740</td> <td>5265</td> <td>2</td> <td>0,84</td> <td>2082</td> <td>2929</td> <td>2</td> <td>1,42</td> <td>1191</td> <td>1675</td> <td>2</td> <td>2,38</td> <td>635</td> <td>893</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>1662</td> <td>2339</td> <td>3</td> <td>1,25</td> <td>925</td> <td>1302</td> <td>3</td> <td>2,18</td> <td>529</td> <td>745</td> <td>2,5</td> <td>2,97</td> <td>282</td> <td>397</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>935</td> <td>1315</td> <td>4</td> <td>1,70</td> <td>520</td> <td>732</td> <td>4</td> <td>2,91</td> <td>298</td> <td>419</td> <td>3</td> <td>3,56</td> <td>159</td> <td>223</td> </tr> </tbody> </table>										Spot				Medium				Flood				Wideflood						2000lm	3000lm			2000lm	3000lm			2000lm	3000lm			2000lm	3000lm	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	14960	21047	1	0,42	8328	11716	1	0,74	4763	6702	1	1,19	2539	3572	2	0,56	3740	5265	2	0,84	2082	2929	2	1,42	1191	1675	2	2,38	635	893	3	0,84	1662	2339	3	1,25	925	1302	3	2,18	529	745	2,5	2,97	282	397	4	1,12	935	1315	4	1,70	520	732	4	2,91	298	419	3	3,56	159	223
Spot				Medium				Flood				Wideflood																																																																																																													
		2000lm	3000lm			2000lm	3000lm			2000lm	3000lm			2000lm	3000lm																																																																																																										
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																										
1	0,28	14960	21047	1	0,42	8328	11716	1	0,74	4763	6702	1	1,19	2539	3572																																																																																																										
2	0,56	3740	5265	2	0,84	2082	2929	2	1,42	1191	1675	2	2,38	635	893																																																																																																										
3	0,84	1662	2339	3	1,25	925	1302	3	2,18	529	745	2,5	2,97	282	397																																																																																																										
4	1,12	935	1315	4	1,70	520	732	4	2,91	298	419	3	3,56	159	223																																																																																																										
<p>3000K 930 Spectral power distributions</p>																																																																																																																									
NEUTRAL WHITE 4000K (940)																																																																																																																									
SIDECAR S Pro 2000lm SP 940	Spot 15°	4000K	92	2460	19W	2280	119	213150	213154																																																																																																																
SIDECAR S Pro 2000lm ME 940	Medium 25°	4000K	92	2460	19W	2280	119	213151	213155																																																																																																																
SIDECAR S Pro 2000lm FL 940	Flood 40°	4000K	92	2460	19W	2280	119	213152	213156																																																																																																																
SIDECAR S Pro 2000lm WFL 940	Widefl. 60°	4000K	92	2460	19W	2280	119	213153	213157																																																																																																																
SIDECAR S Pro 3000lm SP 940																																																																																																																									
SIDECAR S Pro 3000lm ME 940	Medium 25°	4000K	92	3350	27W	3080	114	213250	213254																																																																																																																
SIDECAR S Pro 3000lm ME 940	Medium 25°	4000K	92	3350	27W	3080	114	213251	213255																																																																																																																
SIDECAR S Pro 3000lm FL 940	Flood 40°	4000K	92	3350	27W	3080	114	213252	213256																																																																																																																
SIDECAR S Pro 3000lm WFL 940	Widefl. 60°	4000K	92	3350	27W	3080	114	213253	213257																																																																																																																
<table border="1"> <thead> <tr> <th colspan="4">Spot</th> <th colspan="4">Medium</th> <th colspan="4">Flood</th> <th colspan="4">Wideflood</th> </tr> <tr> <th colspan="2"></th> <th>2000lm</th> <th>3000lm</th> <th colspan="2"></th> <th>2000lm</th> <th>3000lm</th> <th colspan="2"></th> <th>2000lm</th> <th>3000lm</th> <th colspan="2"></th> <th>2000lm</th> <th>3000lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>14765</td> <td>19946</td> <td>1</td> <td>0,42</td> <td>8219</td> <td>11103</td> <td>1</td> <td>0,74</td> <td>4701</td> <td>6351</td> <td>1</td> <td>1,19</td> <td>2506</td> <td>3385</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>3691</td> <td>4987</td> <td>2</td> <td>0,84</td> <td>2055</td> <td>2776</td> <td>2</td> <td>1,42</td> <td>1175</td> <td>1588</td> <td>2</td> <td>2,38</td> <td>626</td> <td>846</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>1641</td> <td>2216</td> <td>3</td> <td>1,25</td> <td>913</td> <td>1234</td> <td>3</td> <td>2,18</td> <td>522</td> <td>706</td> <td>2,5</td> <td>2,97</td> <td>278</td> <td>376</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>923</td> <td>1247</td> <td>4</td> <td>1,70</td> <td>514</td> <td>694</td> <td>4</td> <td>2,91</td> <td>294</td> <td>397</td> <td>3</td> <td>3,56</td> <td>157</td> <td>212</td> </tr> </tbody> </table>										Spot				Medium				Flood				Wideflood						2000lm	3000lm			2000lm	3000lm			2000lm	3000lm			2000lm	3000lm	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	14765	19946	1	0,42	8219	11103	1	0,74	4701	6351	1	1,19	2506	3385	2	0,56	3691	4987	2	0,84	2055	2776	2	1,42	1175	1588	2	2,38	626	846	3	0,84	1641	2216	3	1,25	913	1234	3	2,18	522	706	2,5	2,97	278	376	4	1,12	923	1247	4	1,70	514	694	4	2,91	294	397	3	3,56	157	212
Spot				Medium				Flood				Wideflood																																																																																																													
		2000lm	3000lm			2000lm	3000lm			2000lm	3000lm			2000lm	3000lm																																																																																																										
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																										
1	0,28	14765	19946	1	0,42	8219	11103	1	0,74	4701	6351	1	1,19	2506	3385																																																																																																										
2	0,56	3691	4987	2	0,84	2055	2776	2	1,42	1175	1588	2	2,38	626	846																																																																																																										
3	0,84	1641	2216	3	1,25	913	1234	3	2,18	522	706	2,5	2,97	278	376																																																																																																										
4	1,12	923	1247	4	1,70	514	694	4	2,91	294	397	3	3,56	157	212																																																																																																										
<p>4000K 940 Spectral power distributions</p>																																																																																																																									

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.