


SIDECAR XS DIM

“Sidecar is our most compact version of spotlights. It is a traditional side-by-side solution, inspired by the sidecar version of a motorcycle. We created a design that places the point of rotation on the track as central as possible to avoid a big offset from the track, allowing a number of spotlights to visually work well together. Developed and produced in Sweden”.

LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral driver.
Dimmable via phase-cut.
Rotation 365°. Vertical adjustment +/- 90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	430g
Reflector	High purity aluminium
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 50pcs/MCB 16A type B
Ripple out. current	< 20%
Colour consistency	3 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Phase-cut 100-20%



- White
- Black

SIDECAR XS DIM

Description	Reflector	CCT (K)	CRI	Lumen	Load	Lumen	Lm/W	○ White	● Black																																			
					LIGHTSOURCE	LUMINAIRE	ART. No.																																					
WARM WHITE 2700K (927)																																												
SIDECAR XS Dim 1000lm ME 927 Medium 25°		2700K	92	1055	10W	930	93	211121	211125																																			
SIDECAR XS Dim 1000lm FL 927 Flood 40°		2700K	92	1055	10W	930	93	211122	211126																																			
	<table border="1"> <thead> <tr> <th colspan="3">Medium 25°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr><td>1</td><td>0,44</td><td>3660</td></tr> <tr><td>2</td><td>0,88</td><td>915</td></tr> <tr><td>3</td><td>1,32</td><td>407</td></tr> <tr><td>4</td><td>1,76</td><td>229</td></tr> </tbody> </table>	Medium 25°			m	∅	Lux	1	0,44	3660	2	0,88	915	3	1,32	407	4	1,76	229	<table border="1"> <thead> <tr> <th colspan="3">Flood 40°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr><td>1</td><td>0,70</td><td>1995</td></tr> <tr><td>2</td><td>1,41</td><td>499</td></tr> <tr><td>3</td><td>2,11</td><td>222</td></tr> <tr><td>4</td><td>2,81</td><td>125</td></tr> </tbody> </table>	Flood 40°			m	∅	Lux	1	0,70	1995	2	1,41	499	3	2,11	222	4	2,81	125	<p>2700K 927 Spectral power distributions</p>					
Medium 25°																																												
m	∅	Lux																																										
1	0,44	3660																																										
2	0,88	915																																										
3	1,32	407																																										
4	1,76	229																																										
Flood 40°																																												
m	∅	Lux																																										
1	0,70	1995																																										
2	1,41	499																																										
3	2,11	222																																										
4	2,81	125																																										
WARM WHITE 3000K (930)																																												
SIDECAR XS Dim 1000lm ME 930 Medium 25°		3000K	92	1220	10W	1070	107	211111	211115																																			
SIDECAR XS Dim 1000lm FL 930 Flood 40°		3000K	92	1220	10W	1070	107	211112	211116																																			
	<table border="1"> <thead> <tr> <th colspan="3">Medium 25°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr><td>1</td><td>0,44</td><td>4210</td></tr> <tr><td>2</td><td>0,88</td><td>1053</td></tr> <tr><td>3</td><td>1,32</td><td>468</td></tr> <tr><td>4</td><td>1,76</td><td>263</td></tr> </tbody> </table>	Medium 25°			m	∅	Lux	1	0,44	4210	2	0,88	1053	3	1,32	468	4	1,76	263	<table border="1"> <thead> <tr> <th colspan="3">Flood 40°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr><td>1</td><td>0,70</td><td>2295</td></tr> <tr><td>2</td><td>1,41</td><td>574</td></tr> <tr><td>3</td><td>2,11</td><td>255</td></tr> <tr><td>4</td><td>2,81</td><td>143</td></tr> </tbody> </table>	Flood 40°			m	∅	Lux	1	0,70	2295	2	1,41	574	3	2,11	255	4	2,81	143	<p>3000K 930 Spectral power distributions</p>					
Medium 25°																																												
m	∅	Lux																																										
1	0,44	4210																																										
2	0,88	1053																																										
3	1,32	468																																										
4	1,76	263																																										
Flood 40°																																												
m	∅	Lux																																										
1	0,70	2295																																										
2	1,41	574																																										
3	2,11	255																																										
4	2,81	143																																										
NEUTRAL WHITE 4000K (940)																																												
SIDECAR XS Dim 1000lm ME 940 Medium 25°		4000K	92	1185	10W	1040	104	211151	211155																																			
SIDECAR XS Dim 1000lm FL 940 Flood 40°		4000K	92	1185	10W	1040	104	211152	211156																																			
	<table border="1"> <thead> <tr> <th colspan="3">Medium 25°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr><td>1</td><td>0,44</td><td>4092</td></tr> <tr><td>2</td><td>0,88</td><td>1023</td></tr> <tr><td>3</td><td>1,32</td><td>455</td></tr> <tr><td>4</td><td>1,76</td><td>256</td></tr> </tbody> </table>	Medium 25°			m	∅	Lux	1	0,44	4092	2	0,88	1023	3	1,32	455	4	1,76	256	<table border="1"> <thead> <tr> <th colspan="3">Flood 40°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr><td>1</td><td>0,70</td><td>2231</td></tr> <tr><td>2</td><td>1,41</td><td>558</td></tr> <tr><td>3</td><td>2,11</td><td>248</td></tr> <tr><td>4</td><td>2,81</td><td>139</td></tr> </tbody> </table>	Flood 40°			m	∅	Lux	1	0,70	2231	2	1,41	558	3	2,11	248	4	2,81	139	<p>4000K 940 Spectral power distributions</p>					
Medium 25°																																												
m	∅	Lux																																										
1	0,44	4092																																										
2	0,88	1023																																										
3	1,32	455																																										
4	1,76	256																																										
Flood 40°																																												
m	∅	Lux																																										
1	0,70	2231																																										
2	1,41	558																																										
3	2,11	248																																										
4	2,81	139																																										

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/- 150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.