


# MOCCA M PRO

“Mocca - The all-in-one cylindrical solution. Mocca is our interpretation of an all integrated cylindrical spotlight. The cooling is passive, being all silent, by allowing cold air to flow from the middle of the cylinder and out in the back. By choosing Mocca you will get a uncluttered environment focusing on the essential: The simplicity of the spotlight and the effect of the light. Developed and produced in Sweden”.

LED-spotlight with passive cooling system.  
Die cast aluminium body, powder coat painted.  
Integral heatsink. Integral premium driver.  
Low ripple output current <4% to assure camera and scanner friendly performance.  
Rotation 365°. Vertical adjustment 0-90°.  
Track mounted with 3-circuit adapter.



<b>Class of protection</b>	IP20, class I
<b>Colours</b>	White, black
<b>Weight total</b>	1120g
<b>Reflector</b>	High efficiency metalized PC
<b>Lifetime</b>	50.000h L80/B10 at Ta 25°C
<b>Mounting</b>	3-circuit universal adaptor
<b>Voltage</b>	220-240V 50/60hz
<b>Qty per MCB</b>	Max 34pcs/MCB 16A type B
<b>Ripple out. current</b>	< 4%. Flicker-free performance
<b>Colour consistency</b>	3 SDCM
<b>Photobiological safety</b>	RG1
<b>Design</b>	Jesper Ståhl
<b>Dimming</b>	Not dimmable



- White
- Black

# MOCCA M PRO

Description	Reflector	CCT (K)	CRI	Load	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																						
LIGHTSOURCE						LUMINAIRE			ART. No.																																																							
WARM WHITE 3000K (930)																																																																
MOCCA M Pro 3500lm SP 930	Spot 15°	3000K	92	27W	3720	31W	3340	108	<b>224310</b>	<b>224314</b>																																																						
MOCCA M Pro 3500lm ME 930	Medium 25°	3000K	92	27W	3720	31W	3340	108	<b>224311</b>	<b>224315</b>																																																						
MOCCA M Pro 3500lm FL 930	Flood 45°	3000K	92	27W	3720	31W	3340	108	<b>224312</b>	<b>224316</b>																																																						
<table border="1"> <thead> <tr> <th colspan="3">Spot 15°</th> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 45°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,26</td> <td>21752</td> <td>1</td> <td>0,43</td> <td>10559</td> <td>1</td> <td>0,86</td> <td>4777</td> </tr> <tr> <td>2</td> <td>0,53</td> <td>5438</td> <td>2</td> <td>0,86</td> <td>2640</td> <td>2</td> <td>1,72</td> <td>1194</td> </tr> <tr> <td>3</td> <td>0,79</td> <td>2417</td> <td>3</td> <td>1,30</td> <td>1173</td> <td>3</td> <td>2,58</td> <td>531</td> </tr> <tr> <td>4</td> <td>1,06</td> <td>1360</td> <td>4</td> <td>1,72</td> <td>660</td> <td>4</td> <td>3,44</td> <td>299</td> </tr> </tbody> </table>						Spot 15°			Medium 25°			Flood 45°			m	∅	Lux	m	∅	Lux	m	∅	Lux	1	0,26	21752	1	0,43	10559	1	0,86	4777	2	0,53	5438	2	0,86	2640	2	1,72	1194	3	0,79	2417	3	1,30	1173	3	2,58	531	4	1,06	1360	4	1,72	660	4	3,44	299	<p><b>3000K 930</b> Spectral power distributions</p>				
Spot 15°			Medium 25°			Flood 45°																																																										
m	∅	Lux	m	∅	Lux	m	∅	Lux																																																								
1	0,26	21752	1	0,43	10559	1	0,86	4777																																																								
2	0,53	5438	2	0,86	2640	2	1,72	1194																																																								
3	0,79	2417	3	1,30	1173	3	2,58	531																																																								
4	1,06	1360	4	1,72	660	4	3,44	299																																																								
NEUTRAL WHITE 4000K (940)																																																																
MOCCA M Pro 3500lm SP 940	Spot 15°	4000K	92	27W	4040	31W	3636	117	<b>224350</b>	<b>224354</b>																																																						
MOCCA M Pro 3500lm ME 940	Medium 25°	4000K	92	27W	4070	31W	3635	117	<b>224351</b>	<b>224355</b>																																																						
MOCCA M Pro 3500lm FL 940	Flood 45°	4000K	92	27W	4040	31W	3635	117	<b>224352</b>	<b>224356</b>																																																						
<table border="1"> <thead> <tr> <th colspan="3">Spot 15°</th> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 45°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,26</td> <td>23628</td> <td>1</td> <td>0,43</td> <td>11487</td> <td>1</td> <td>0,86</td> <td>5186</td> </tr> <tr> <td>2</td> <td>0,53</td> <td>5907</td> <td>2</td> <td>0,86</td> <td>2872</td> <td>2</td> <td>1,72</td> <td>1296</td> </tr> <tr> <td>3</td> <td>0,79</td> <td>3625</td> <td>3</td> <td>1,30</td> <td>1276</td> <td>3</td> <td>2,58</td> <td>576</td> </tr> <tr> <td>4</td> <td>1,06</td> <td>1495</td> <td>4</td> <td>1,72</td> <td>718</td> <td>4</td> <td>3,44</td> <td>324</td> </tr> </tbody> </table>						Spot 15°			Medium 25°			Flood 45°			m	∅	Lux	m	∅	Lux	m	∅	Lux	1	0,26	23628	1	0,43	11487	1	0,86	5186	2	0,53	5907	2	0,86	2872	2	1,72	1296	3	0,79	3625	3	1,30	1276	3	2,58	576	4	1,06	1495	4	1,72	718	4	3,44	324	<p><b>4000K 940</b> Spectral power distributions</p>				
Spot 15°			Medium 25°			Flood 45°																																																										
m	∅	Lux	m	∅	Lux	m	∅	Lux																																																								
1	0,26	23628	1	0,43	11487	1	0,86	5186																																																								
2	0,53	5907	2	0,86	2872	2	1,72	1296																																																								
3	0,79	3625	3	1,30	1276	3	2,58	576																																																								
4	1,06	1495	4	1,72	718	4	3,44	324																																																								

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.