


MOCCA M PRO

“Mocca - The all-in-one cylindrical solution. Mocca is our interpretation of an all integrated cylindrical spotlight. The cooling is passive, being all silent, by allowing cold air to flow from the middle of the cylinder and out in the back. By choosing Mocca you will get a uncluttered environment focusing on the essential: The simplicity of the spotlight and the effect of the light. Developed and produced in Sweden”.

LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral premium driver.
Low ripple output current <4% to assure camera and scanner friendly performance.
Rotation 365°. Vertical adjustment 0-90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	1120g
Reflector	High efficiency metalized PC
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 34pcs/MCB 16A type B
Ripple out. current	< 4%. Flicker-free performance
Colour consistency	3 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Not dimmable



- White
- Black

MOCCA M PRO

Description	Reflector	CCT (K)	CRI	Load	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																		
LIGHTSOURCE						LUMINAIRE			ART. No.																																																			
WARM WHITE 3000K (830)																																																												
MOCCA M Pro 3500lm SP 830	Spot 15°	3000K	82	23W	3420	27W	3150	106	224300	224304																																																		
MOCCA M Pro 3500lm ME 830	Medium 25°	3000K	82	23W	3420	27W	3150	106	224301	224305																																																		
MOCCA M Pro 3500lm FL 830	Flood 45°	3000K	82	23W	3420	27W	3150	106	224302	224306																																																		
<table border="1"> <thead> <tr> <th colspan="3">Spot 15°</th> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 45°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,23</td> <td>20658</td> <td>1</td> <td>0,43</td> <td>9956</td> <td>1</td> <td>0,86</td> <td>4451</td> </tr> <tr> <td>2</td> <td>0,53</td> <td>5165</td> <td>2</td> <td>0,86</td> <td>2489</td> <td>2</td> <td>1,72</td> <td>1113</td> </tr> <tr> <td>3</td> <td>0,79</td> <td>2295</td> <td>3</td> <td>1,30</td> <td>1106</td> <td>3</td> <td>2,58</td> <td>495</td> </tr> <tr> <td>4</td> <td>1,06</td> <td>1291</td> <td>4</td> <td>1,72</td> <td>622</td> <td>4</td> <td>3,44</td> <td>278</td> </tr> </tbody> </table>			Spot 15°			Medium 25°			Flood 45°			m	∅	Lux	m	∅	Lux	m	∅	Lux	1	0,23	20658	1	0,43	9956	1	0,86	4451	2	0,53	5165	2	0,86	2489	2	1,72	1113	3	0,79	2295	3	1,30	1106	3	2,58	495	4	1,06	1291	4	1,72	622	4	3,44	278	<p>3000K 830 Spectral power distributions</p>			
Spot 15°			Medium 25°			Flood 45°																																																						
m	∅	Lux	m	∅	Lux	m	∅	Lux																																																				
1	0,23	20658	1	0,43	9956	1	0,86	4451																																																				
2	0,53	5165	2	0,86	2489	2	1,72	1113																																																				
3	0,79	2295	3	1,30	1106	3	2,58	495																																																				
4	1,06	1291	4	1,72	622	4	3,44	278																																																				
WARM WHITE 3000K (930)																																																												
MOCCA M Pro 3500lm SP 930	Spot 15°	3000K	92	27W	3360	31W	2970	90	224310	224314																																																		
MOCCA M Pro 3500lm ME 930	Medium 25°	3000K	92	27W	3360	31W	2970	90	224311	224315																																																		
MOCCA M Pro 3500lm FL 930	Flood 45°	3000K	92	27W	3360	31W	2970	90	224312	224316																																																		
<table border="1"> <thead> <tr> <th colspan="3">Spot 15°</th> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 45°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,23</td> <td>20072</td> <td>1</td> <td>0,43</td> <td>9956</td> <td>1</td> <td>0,86</td> <td>4423</td> </tr> <tr> <td>2</td> <td>0,53</td> <td>5018</td> <td>2</td> <td>0,86</td> <td>2489</td> <td>2</td> <td>1,72</td> <td>1106</td> </tr> <tr> <td>3</td> <td>0,79</td> <td>2230</td> <td>3</td> <td>1,30</td> <td>1106</td> <td>3</td> <td>2,58</td> <td>491</td> </tr> <tr> <td>4</td> <td>1,06</td> <td>1255</td> <td>4</td> <td>1,72</td> <td>622</td> <td>4</td> <td>3,44</td> <td>276</td> </tr> </tbody> </table>			Spot 15°			Medium 25°			Flood 45°			m	∅	Lux	m	∅	Lux	m	∅	Lux	1	0,23	20072	1	0,43	9956	1	0,86	4423	2	0,53	5018	2	0,86	2489	2	1,72	1106	3	0,79	2230	3	1,30	1106	3	2,58	491	4	1,06	1255	4	1,72	622	4	3,44	276	<p>3000K 930 Spectral power distributions</p>			
Spot 15°			Medium 25°			Flood 45°																																																						
m	∅	Lux	m	∅	Lux	m	∅	Lux																																																				
1	0,23	20072	1	0,43	9956	1	0,86	4423																																																				
2	0,53	5018	2	0,86	2489	2	1,72	1106																																																				
3	0,79	2230	3	1,30	1106	3	2,58	491																																																				
4	1,06	1255	4	1,72	622	4	3,44	276																																																				
NEUTRAL WHITE 4000K (840)																																																												
MOCCA M Pro 3500lm SP 840	Spot 15°	4000K	82	23W	3630	27W	3270	113	224340	224344																																																		
MOCCA M Pro 3500lm ME 840	Medium 25°	4000K	82	23W	3630	27W	3270	113	224341	224345																																																		
MOCCA M Pro 3500lm FL 840	Flood 45°	4000K	82	23W	3630	27W	3270	113	224342	224346																																																		
<table border="1"> <thead> <tr> <th colspan="3">Spot 15°</th> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 45°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,23</td> <td>21439</td> <td>1</td> <td>0,43</td> <td>10389</td> <td>1</td> <td>0,86</td> <td>4687</td> </tr> <tr> <td>2</td> <td>0,53</td> <td>5360</td> <td>2</td> <td>0,86</td> <td>2597</td> <td>2</td> <td>1,72</td> <td>1172</td> </tr> <tr> <td>3</td> <td>0,79</td> <td>2382</td> <td>3</td> <td>1,30</td> <td>1154</td> <td>3</td> <td>2,58</td> <td>521</td> </tr> <tr> <td>4</td> <td>1,06</td> <td>1340</td> <td>4</td> <td>1,72</td> <td>649</td> <td>4</td> <td>3,44</td> <td>293</td> </tr> </tbody> </table>			Spot 15°			Medium 25°			Flood 45°			m	∅	Lux	m	∅	Lux	m	∅	Lux	1	0,23	21439	1	0,43	10389	1	0,86	4687	2	0,53	5360	2	0,86	2597	2	1,72	1172	3	0,79	2382	3	1,30	1154	3	2,58	521	4	1,06	1340	4	1,72	649	4	3,44	293	<p>4000K 840 Spectral power distributions</p>			
Spot 15°			Medium 25°			Flood 45°																																																						
m	∅	Lux	m	∅	Lux	m	∅	Lux																																																				
1	0,23	21439	1	0,43	10389	1	0,86	4687																																																				
2	0,53	5360	2	0,86	2597	2	1,72	1172																																																				
3	0,79	2382	3	1,30	1154	3	2,58	521																																																				
4	1,06	1340	4	1,72	649	4	3,44	293																																																				
NEUTRAL WHITE 4000K (940)																																																												
MOCCA M Pro 3500lm SP 940	Spot 15°	4000K	92	27W	3295	31W	2935	99	224350	224354																																																		
MOCCA M Pro 3500lm ME 940	Medium 25°	4000K	92	27W	3295	31W	2935	99	224351	224355																																																		
MOCCA M Pro 3500lm FL 940	Flood 45°	4000K	92	27W	3295	31W	2935	99	224352	224356																																																		
<table border="1"> <thead> <tr> <th colspan="3">Spot 15°</th> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 45°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,23</td> <td>19114</td> <td>1</td> <td>0,43</td> <td>9268</td> <td>1</td> <td>0,86</td> <td>4190</td> </tr> <tr> <td>2</td> <td>0,53</td> <td>4779</td> <td>2</td> <td>0,86</td> <td>2317</td> <td>2</td> <td>1,72</td> <td>1048</td> </tr> <tr> <td>3</td> <td>0,79</td> <td>2124</td> <td>3</td> <td>1,30</td> <td>1030</td> <td>3</td> <td>2,58</td> <td>466</td> </tr> <tr> <td>4</td> <td>1,06</td> <td>1195</td> <td>4</td> <td>1,72</td> <td>579</td> <td>4</td> <td>3,44</td> <td>262</td> </tr> </tbody> </table>			Spot 15°			Medium 25°			Flood 45°			m	∅	Lux	m	∅	Lux	m	∅	Lux	1	0,23	19114	1	0,43	9268	1	0,86	4190	2	0,53	4779	2	0,86	2317	2	1,72	1048	3	0,79	2124	3	1,30	1030	3	2,58	466	4	1,06	1195	4	1,72	579	4	3,44	262	<p>4000K 940 Spectral power distributions</p>			
Spot 15°			Medium 25°			Flood 45°																																																						
m	∅	Lux	m	∅	Lux	m	∅	Lux																																																				
1	0,23	19114	1	0,43	9268	1	0,86	4190																																																				
2	0,53	4779	2	0,86	2317	2	1,72	1048																																																				
3	0,79	2124	3	1,30	1030	3	2,58	466																																																				
4	1,06	1195	4	1,72	579	4	3,44	262																																																				

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.