


# SIDECAR S PRO

“Sidecar is our most compact version of spotlights. It is a traditional side-by-side solution, inspired by the sidecar version of a motorcycle. We created a design that places the point of rotation on the track as central as possible to avoid a big offset from the track, allowing a number of spotlights to visually work well together. Developed and produced in Sweden”.

LED-spotlight with passive cooling system.  
Die cast aluminium body, powder coat painted.  
Integral heatsink. Integral premium driver.  
Low ripple output current <4% to assure camera and scanner friendly performance.  
Rotation 365°. Vertical adjustment +/- 90°.  
Track mounted with 3-circuit adaptor.



<b>Class of protection</b>	IP20, class I
<b>Colours</b>	White, black
<b>Weight total</b>	760g
<b>Reflector</b>	High purity aluminium
<b>Lifetime</b>	50.000h L80/B10 at Ta 25°C
<b>Mounting</b>	3-circuit universal adaptor
<b>Voltage</b>	220-240V 50/60hz
<b>Qty per MCB</b>	Max 34pcs/MCB 16A type B
<b>Ripple out. current</b>	< 4%. Flicker-free performance
<b>Colour consistency</b>	3 SDCM
<b>Photobiological safety</b>	RG1
<b>Design</b>	Jesper Ståhl
<b>Dimming</b>	Not dimmable



- White
- Black

# SIDECAR S PRO

Description	Reflector	CCT (K)	CRI	Load	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																																																																																																																																																
LIGHTSOURCE						LUMINAIRE			ART. No.																																																																																																																																																																																	
WARM WHITE 3000K (930)																																																																																																																																																																																										
SIDECAR S Pro 2000lm SP 930	Spot 15°	3000K	92	16W	2280	19W	2110	110	<b>213110</b>	<b>213114</b>																																																																																																																																																																																
SIDECAR S Pro 2000lm ME 930	Medium 25°	3000K	92	16W	2280	19W	2110	110	<b>213111</b>	<b>213115</b>																																																																																																																																																																																
SIDECAR S Pro 2000lm FL 930	Flood 40°	3000K	92	16W	2280	19W	2110	110	<b>213112</b>	<b>213116</b>																																																																																																																																																																																
SIDECAR S Pro 2000lm WFL 930	Widefl. 60°	3000K	92	16W	2280	19W	2020	106	<b>213113</b>	<b>213117</b>																																																																																																																																																																																
SIDECAR S Pro 3000lm SP 930	Spot 15°	3000K	92	23W	3110	27W	2860	106	<b>213210</b>	<b>213214</b>																																																																																																																																																																																
SIDECAR S Pro 3000lm ME 930	Medium 25°	3000K	92	23W	3110	27W	2860	106	<b>213211</b>	<b>213215</b>																																																																																																																																																																																
SIDECAR S Pro 3000lm FL 930	Flood 40°	3000K	92	23W	3110	27W	2860	106	<b>213212</b>	<b>213216</b>																																																																																																																																																																																
SIDECAR S Pro 3000lm WFL 930	Widefl. 60°	3000K	92	23W	3110	27W	2735	101	<b>213213</b>	<b>213217</b>																																																																																																																																																																																
<table border="1"> <thead> <tr> <th colspan="2">Spot</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2">Medium</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2">Flood</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2">Wideflood</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>13665</td> <td>18521</td> <td>1</td> <td>0,42</td> <td>7606</td> <td>10310</td> <td>1</td> <td>0,74</td> <td>4786</td> <td>6487</td> <td>1</td> <td>1,19</td> <td>2217</td> <td>3005</td> <td>1</td> <td>0,28</td> <td>14701</td> <td>19925</td> <td>1</td> <td>0,42</td> <td>8193</td> <td>11105</td> <td>1</td> <td>0,74</td> <td>5163</td> <td>6998</td> <td>1</td> <td>1,19</td> <td>2388</td> <td>3236</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>3416</td> <td>4630</td> <td>2</td> <td>0,84</td> <td>1901</td> <td>2578</td> <td>2</td> <td>1,42</td> <td>1196</td> <td>1622</td> <td>2</td> <td>2,38</td> <td>554</td> <td>751</td> <td>2</td> <td>0,56</td> <td>3675</td> <td>4981</td> <td>2</td> <td>0,84</td> <td>2048</td> <td>2776</td> <td>2</td> <td>1,42</td> <td>1291</td> <td>1750</td> <td>2</td> <td>2,38</td> <td>597</td> <td>809</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>1518</td> <td>2058</td> <td>3</td> <td>1,25</td> <td>845</td> <td>1146</td> <td>3</td> <td>2,18</td> <td>532</td> <td>721</td> <td>3</td> <td>3,56</td> <td>246</td> <td>334</td> <td>3</td> <td>0,84</td> <td>1633</td> <td>2214</td> <td>3</td> <td>1,25</td> <td>910</td> <td>1234</td> <td>3</td> <td>2,18</td> <td>574</td> <td>778</td> <td>3</td> <td>2,97</td> <td>265</td> <td>360</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>854</td> <td>1158</td> <td>4</td> <td>1,70</td> <td>475</td> <td>644</td> <td>4</td> <td>2,91</td> <td>299</td> <td>405</td> <td>4</td> <td>3,56</td> <td>139</td> <td>188</td> <td>4</td> <td>1,12</td> <td>919</td> <td>1245</td> <td>4</td> <td>1,70</td> <td>512</td> <td>694</td> <td>4</td> <td>2,91</td> <td>323</td> <td>437</td> <td>4</td> <td>3,56</td> <td>149</td> <td>202</td> </tr> </tbody> </table>											Spot		2000lm		3000lm		Medium		2000lm		3000lm		Flood		2000lm		3000lm		Wideflood		2000lm		3000lm		m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	13665	18521	1	0,42	7606	10310	1	0,74	4786	6487	1	1,19	2217	3005	1	0,28	14701	19925	1	0,42	8193	11105	1	0,74	5163	6998	1	1,19	2388	3236	2	0,56	3416	4630	2	0,84	1901	2578	2	1,42	1196	1622	2	2,38	554	751	2	0,56	3675	4981	2	0,84	2048	2776	2	1,42	1291	1750	2	2,38	597	809	3	0,84	1518	2058	3	1,25	845	1146	3	2,18	532	721	3	3,56	246	334	3	0,84	1633	2214	3	1,25	910	1234	3	2,18	574	778	3	2,97	265	360	4	1,12	854	1158	4	1,70	475	644	4	2,91	299	405	4	3,56	139	188	4	1,12	919	1245	4	1,70	512	694	4	2,91	323	437	4	3,56	149	202
Spot		2000lm		3000lm		Medium		2000lm		3000lm		Flood		2000lm		3000lm		Wideflood		2000lm		3000lm																																																																																																																																																																				
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																																																			
1	0,28	13665	18521	1	0,42	7606	10310	1	0,74	4786	6487	1	1,19	2217	3005	1	0,28	14701	19925	1	0,42	8193	11105	1	0,74	5163	6998	1	1,19	2388	3236																																																																																																																																																											
2	0,56	3416	4630	2	0,84	1901	2578	2	1,42	1196	1622	2	2,38	554	751	2	0,56	3675	4981	2	0,84	2048	2776	2	1,42	1291	1750	2	2,38	597	809																																																																																																																																																											
3	0,84	1518	2058	3	1,25	845	1146	3	2,18	532	721	3	3,56	246	334	3	0,84	1633	2214	3	1,25	910	1234	3	2,18	574	778	3	2,97	265	360																																																																																																																																																											
4	1,12	854	1158	4	1,70	475	644	4	2,91	299	405	4	3,56	139	188	4	1,12	919	1245	4	1,70	512	694	4	2,91	323	437	4	3,56	149	202																																																																																																																																																											
NEUTRAL WHITE 4000K (940)																																																																																																																																																																																										
SIDECAR S Pro 2000lm SP 940	Spot 15°	4000K	92	16W	2460	19W	2280	119	<b>213150</b>	<b>213154</b>																																																																																																																																																																																
SIDECAR S Pro 2000lm ME 940	Medium 25°	4000K	92	16W	2460	19W	2280	119	<b>213151</b>	<b>213155</b>																																																																																																																																																																																
SIDECAR S Pro 2000lm FL 940	Flood 40°	4000K	92	16W	2460	19W	2280	119	<b>213152</b>	<b>213156</b>																																																																																																																																																																																
SIDECAR S Pro 2000lm WFL 940	Widefl. 60°	4000K	92	16W	2460	19W	2190	114	<b>213153</b>	<b>213157</b>																																																																																																																																																																																
SIDECAR S Pro 3000lm SP 940	Spot 15°	4000K	92	23W	3350	27W	3080	114	<b>213250</b>	<b>213254</b>																																																																																																																																																																																
SIDECAR S Pro 3000lm ME 940	Medium 25°	4000K	92	23W	3350	27W	3080	114	<b>213251</b>	<b>213255</b>																																																																																																																																																																																
SIDECAR S Pro 3000lm FL 940	Flood 40°	4000K	92	23W	3350	27W	3080	114	<b>213252</b>	<b>213256</b>																																																																																																																																																																																
SIDECAR S Pro 3000lm WFL 940	Widefl. 60°	4000K	92	23W	3350	27W	2945	109	<b>213253</b>	<b>213257</b>																																																																																																																																																																																
<table border="1"> <thead> <tr> <th colspan="2">Spot</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2">Medium</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2">Flood</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2">Wideflood</th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>14701</td> <td>19925</td> <td>1</td> <td>0,42</td> <td>8193</td> <td>11105</td> <td>1</td> <td>0,74</td> <td>5163</td> <td>6998</td> <td>1</td> <td>1,19</td> <td>2388</td> <td>3236</td> <td>1</td> <td>0,28</td> <td>14701</td> <td>19925</td> <td>1</td> <td>0,42</td> <td>8193</td> <td>11105</td> <td>1</td> <td>0,74</td> <td>5163</td> <td>6998</td> <td>1</td> <td>1,19</td> <td>2388</td> <td>3236</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>3675</td> <td>4981</td> <td>2</td> <td>0,84</td> <td>2048</td> <td>2776</td> <td>2</td> <td>1,42</td> <td>1291</td> <td>1750</td> <td>2</td> <td>2,38</td> <td>597</td> <td>809</td> <td>2</td> <td>0,56</td> <td>3675</td> <td>4981</td> <td>2</td> <td>0,84</td> <td>2048</td> <td>2776</td> <td>2</td> <td>1,42</td> <td>1291</td> <td>1750</td> <td>2</td> <td>2,38</td> <td>597</td> <td>809</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>1633</td> <td>2214</td> <td>3</td> <td>1,25</td> <td>910</td> <td>1234</td> <td>3</td> <td>2,18</td> <td>574</td> <td>778</td> <td>3</td> <td>3,56</td> <td>265</td> <td>360</td> <td>3</td> <td>0,84</td> <td>1633</td> <td>2214</td> <td>3</td> <td>1,25</td> <td>910</td> <td>1234</td> <td>3</td> <td>2,18</td> <td>574</td> <td>778</td> <td>3</td> <td>2,97</td> <td>265</td> <td>360</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>919</td> <td>1245</td> <td>4</td> <td>1,70</td> <td>512</td> <td>694</td> <td>4</td> <td>2,91</td> <td>323</td> <td>437</td> <td>4</td> <td>3,56</td> <td>149</td> <td>202</td> <td>4</td> <td>1,12</td> <td>919</td> <td>1245</td> <td>4</td> <td>1,70</td> <td>512</td> <td>694</td> <td>4</td> <td>2,91</td> <td>323</td> <td>437</td> <td>4</td> <td>3,56</td> <td>149</td> <td>202</td> </tr> </tbody> </table>											Spot		2000lm		3000lm		Medium		2000lm		3000lm		Flood		2000lm		3000lm		Wideflood		2000lm		3000lm		m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	14701	19925	1	0,42	8193	11105	1	0,74	5163	6998	1	1,19	2388	3236	1	0,28	14701	19925	1	0,42	8193	11105	1	0,74	5163	6998	1	1,19	2388	3236	2	0,56	3675	4981	2	0,84	2048	2776	2	1,42	1291	1750	2	2,38	597	809	2	0,56	3675	4981	2	0,84	2048	2776	2	1,42	1291	1750	2	2,38	597	809	3	0,84	1633	2214	3	1,25	910	1234	3	2,18	574	778	3	3,56	265	360	3	0,84	1633	2214	3	1,25	910	1234	3	2,18	574	778	3	2,97	265	360	4	1,12	919	1245	4	1,70	512	694	4	2,91	323	437	4	3,56	149	202	4	1,12	919	1245	4	1,70	512	694	4	2,91	323	437	4	3,56	149	202
Spot		2000lm		3000lm		Medium		2000lm		3000lm		Flood		2000lm		3000lm		Wideflood		2000lm		3000lm																																																																																																																																																																				
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																																																			
1	0,28	14701	19925	1	0,42	8193	11105	1	0,74	5163	6998	1	1,19	2388	3236	1	0,28	14701	19925	1	0,42	8193	11105	1	0,74	5163	6998	1	1,19	2388	3236																																																																																																																																																											
2	0,56	3675	4981	2	0,84	2048	2776	2	1,42	1291	1750	2	2,38	597	809	2	0,56	3675	4981	2	0,84	2048	2776	2	1,42	1291	1750	2	2,38	597	809																																																																																																																																																											
3	0,84	1633	2214	3	1,25	910	1234	3	2,18	574	778	3	3,56	265	360	3	0,84	1633	2214	3	1,25	910	1234	3	2,18	574	778	3	2,97	265	360																																																																																																																																																											
4	1,12	919	1245	4	1,70	512	694	4	2,91	323	437	4	3,56	149	202	4	1,12	919	1245	4	1,70	512	694	4	2,91	323	437	4	3,56	149	202																																																																																																																																																											

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.